

KOMATSU

Hydraulic Excavator

PC240LC-8

Net engine power SAE J 1349:

125 kW/ 168 hp @ 2,000 rpm

Operating weight:

25,400 kg / 55,997 lb

Working equipment:

Boom length: 5,900 mm

Arm length: 2,500 mm

Bucket capacity (heaped SAE):

1.73 m³ @ 1.5 t/m³



Origin Japan / KLTD

Photos of the equipment are referential and may include optional equipment.

Main technical information

»KOMATSU SAA6D140E-5 engine:

»Net engine power SAE J 1349: 125 kW/ 168 hp @ 2,000 rpm.

»Diesel, turbocharged and aftercooled.

»Displacement: 6.69 L.

»In-line 6-cylinder.

»US EPA Tier III / EU Stage 3A (equivalent) emissions certified).

»Operating weight: 25,400kg / 55,997 lb.



Working equipment

»Working equipment:

»Boom length: 5,900 mm.

»Arm length: 2,500 mm.

»Bucket capacity (heaped SAE):

1.73 m³ @ 1.5 t/m³.

Equipment configuration

»60 Ah alternator.

»2 x 12 V 150 Ah high capacity batteries.

»Cab:

- Soundproof.

- Complies with certification

 - »ROPS (ISO 12117-2/2008).

 - »OPG (ISO 10262-2).

- Air conditioning with climate control.

- Suspension seat.

- The highest safety and comfort standards.

»Boom safety valve.



Operation benefits

»Equipment designed to load topsoil and low density loose material.

»Exceptional bucket capacity of 1.73 m³ allowing for efficient material movement.

»Maintenance accesses designed for easy and quick servicing of the equipment.





New improvement	Benefit
Power and economy operating modes.	Allows you to select the appropriate performance for each type of operation, either in less demanding work ("Economy") or high productivity ("Power").
Idle warning.	To prevent unnecessary fuel consumption, an alarm is displayed on the monitor if the equipment is operating under a certain speed for 5 minutes or more.
Rear view camera.	Provides the operator with visibility to the rear, helping to prevent accidents.
Spacious and quiet cab with ergonomic controls.	Improved operating comfort and performance.



Picture may include optional equipment.

Product designs, specifications and/or data in this document are provided for informational purposes only and are not warranties of any kind. Product designs and/or specifications may be changed at any time without notice. The only warranties that apply to sales of products and services are those stated in the Warranty Policy, which will be furnished upon request.

Komatsu, and related logos, are trademarks of Komatsu Ltd. or one of its subsidiaries.

© Komatsu Ltd. or one of its subsidiaries. All rights reserved.

KOMATSU

For more information, contact your Distributor or visit our website www.komatsulatioamerica.com

KLAT-EQ012/01-2021