

JMHB660H-1

Komatsu Hydraulic Breaker




Power and versatility for all jobsites

- ✓ Maximum impact force since the very first blow.

- Hydraulic accumulator: no more regular nitrogen controls and recharges on jobsites.
- Automatic lubrication: cartridge grease pump mounted on breaker, or tank mounted on excavator.
- Made in France: superior quality steel and manufacturing excellence.
- Dynamic energy adjustment: two working positions automatically adjusted by the breaker.
- Blank firing protection: increased wear parts lifespan.

Weight and dimensions



Weight kg/lb					
Breaker.	3,711	8,181			
+ Mounted tool.	4,067	8,966			
+ Mounted adapter plate (max.)	4,915	10,836			
Dimensions mm/in					
А.	2,514	98.97			
В.	795	31.29			
C.	700	27.55			
D.	550	21.65			
E.	122	4.80			
F.	3,309	130.27			
G.	790	31.10			
H.	1,010	39.76			

Operating Information

- Carrier weight range (min-max, mt) 45 80.
- Oil flow (min-max, I/min / gpm) 280 380 / 74 100.
- Maximum operating pressure (bar/psi) 185 / 2,683.
- Maximum back pressure (bar/psi) 15 / 218.
- Input power (kw) 117.2.
- Striking frequency (min-max, bpm) 300 610.
- Noise level /10m (dba) 95.
- Automatic lubrication standard.
- Soundproofing standard.
- Inspection kit standard.
- Omni-m monitoring system preinstalled.

Options (CPN)

Pressurization kit: 86372505.

• Softstart: 86778818.

• Adapter plate: Upon request.

• Special painting: Upon request.

Maintenance kits (CPN)

• Level 0: 86812963.

• Level 1: 86812971.

• Level 2: 86812989.

Consumables (CPN)

- Grease cartridges (x20) 86784758.
- Em22 grease bucket (20 kg) 86383338.
- Ablf grease bucket (18 kg) 101095008.

Tools				
Diameter (mm/in).	190 / 7.48	190 / 7.48	190 / 7.48	190 / 7.48
Length (mm/in).	1,660 / 63.35	1,660 / 63.35	1,660 / 63.35	1,660 / 63.35
Weight (kg/lb).	336 / 741	324 / 714	341 / 752	356 / 785
CPN.	86780301	86780327	86780285	86780319

The product designs, specifications and information in this document are provided for informational purposes only and do not constitute warranties of any kind. Product designs and specifications may change at any time without prior notice. The only warranties that apply to the sale of products and services are Komatsu's standard written warranties, which will be provided upon request.

Komatsu and other trademarks used in this document are the property of Komatsu Ltd., Komatsu America Corp., Komatsu Mining Corp. or one of their subsidiaries, or their respective owners or licensees.



komatsulatinoamerica.com

