KOMATSU




JMHB670V-1

Komatsu Hydraulic Breaker

Cutting-edge technology ruthless for rocks

- ✓ Designed for 45 to 80 tons carriers.
- ✓ Autonomous working pressure control.
- Hydraulic accumulator: no more regular nitrogen controls and recharges on jobsites.
- Made in France: superior quality steel and manufacturing excellence.
- Operator friendly: blank firing protection, automatic lubrication, energy recovery system, easy maintenance.
- Carrier friendly: anti-vibration dampeners, pressure spikes removal.
- TPS system: improved tool lifespan.

Weight and dimensions



Weight kg/lb					
Breaker.	4,508	9,939			
+ Mounted tool.	4,942	10,896			
+ Mounted adapter plate (max.)	5,969	13,159			
Dimensions mm/in					
Α.	2,709	106.6			
В.	793.5	31.24			
C .	730	28.7			
D.	635	25			
E.	80	3.1			

Operating Information

- Carrier weight range (min-max, mt) 45 80.
- Oil flow (min-max, I/min / gpm) 380 420 / 100.4 111.
- Operating pressure (bar/psi) 165 / 2,393.
- Back pressure (bar/psi) 8 / 116.
- Input power (kw) 115.5.
- Striking frequency (bpm) 380 950.
- Noise level /10m (dba) 100.
- Automatic lubrication standard.
- Soundproofing standard.
- Kit flexibles hp/bp standard.
- Bucket cylinder valve standard.
- Pressurization preinstalled.

Options (CPN)

- Pressurization kit: 86372505.
- Adapter plate: Upon request.
- Special painting: Upon request.

Maintenance kits (CPN)

- Level 0: 86816857.
- Level 1: 86816865.
- Level 2: 86816873.

Consumables (CPN)

- Grease cartridges (x20) 86784758.
- Em22 grease bucket (20 kg) 86383338.
- Ablf grease bucket (18 kg) 101095008.

Tools					
Diameter (mm/in).	202 / 7.95	202 / 7.95	202 / 7.95	202 / 7.95	202 / 7.95
Length (mm/in).	1,800 / 70.86	1,800 / 70.86	1,800 / 70.86	1,800 / 70.86	1,800 / 70.86
Weight (kg/lb).	410 / 904	404 / 891	417 / 919	410 / 904	434 / 957
CPN.	86624061	86624087	86611845	86750403	86624079

The product designs, specifications and information in this document are provided for informational purposes only and do not constitute warranties of any kind. Product designs and specifications may change at any time without prior notice. The only warranties that apply to the sale of products and services are Komatsu's standard written warranties, which will be provided upon request.

Komatsu and other trademarks used in this document are the property of Komatsu Ltd., Komatsu America Corp., Komatsu Mining Corp. or one of their subsidiaries, or their respective owners or licensees.



komatsulatinoamerica.com

