KOMATSU




JMHB460H-1

H-Series Hydraulic Breaker

Power and Versatility for All Jobsites

- ✓ Designed for 35 to 60 ton carriers.
- ✓ Maximum impact power since the very first blow.
- Demolition, quarry, mines and tunnels, mass excavation, landscaping, and recycling. A tool fitted for any situation.
- Hydraulic accumulator: No more regular nitrogen controls and recharges on jobsites.
- Automatic lubrication with 8 kg capacity, mounted on carrier machine.
- Made in France: Superior quality steel, and manufacturing excellence.
- **Dynamic energy adjustment:** Two blowing speeds automatically adjusted.
- Blank firing protection: Increased lifespan of wear parts.

Weight and dimensions



Weight		
Breaker.	3,055 kg.	6,735 lb.
+ Mounted tool.	3,339 kg.	7,361 lb.
+ Mounted adapter plate (max.)	3,852 kg.	8,492 lb.
Dimensiones		
A.	2,329 mm.	91.69 in.
В.	766 mm.	31.25 in.
C.	660 mm.	26 in.
D.	525 mm.	20.66 in.
E.	112 mm.	4.40 in.
F.	3,095 mm.	121.85 in.
G.	790 mm.	31.1 in.
H.	880 mm.	34.64 in.

Operating Information

Carrier weight range (min-max, mt): 35-60

Oil flow (min.max, L/min, gpm): 250-320/66-85

Maximum operating pressure (bar/psi): 185/2,683

Maximum back pressure (bar/psi): 15/218

• Input power (kW): 98.6

Striking frequency (min-max, BPM): 350-700

• Noise level/10 m (dBA): 124

• Automatic lubrication: Standard.

Soundproofing: Standard.Inspection kit: Standard.

• Pressurization: Preinstalled.

Consumables (SKU)

Grease cartridge (5 kg): 86772993
ABL2 grease bucket (24 kg): 86772969
ABLF grease bucket (24 kg): 86772977

Options (SKU)

Pressurization kit: 86372505

• **Softstart:** 86778800

• Adapter plate: Upon request.

• Special painting: Upon request.

Maintenance kits

Basic: Upon request.Level 1: Upon request.Level 2: Upon request.

Tools				
Diameter (mm/in).	174/6.85	174/6.85	174/6.85	174/6.85
Length (mm/in).	1,560/61.42	1,560/61.42	1,560/61.42	1,560/61.42
Weight.	269/594	269/594	271/597	284/626
SKU.	86780251	86780277	86780236	86780269

The designs, specifications and product information in this document are provided only for informative purposes and constitute no warranty whatsoever. Product designs and specifications may change at any time without notice. The only warranties applicable to products and service sales are the standard written warranties, provided by Komatsu upon request.

Komatsu and other brands used in this document are property of Komatsu Ltd., Komatsu America Corp., Komatsu Mining Corp., one of their subsidiaries, or their respective owners or licensees.



komatsulatinoamerica.com

