




JMHB870V-1

Komatsu Hydraulic Breaker

Cutting-edge technology ruthless for rocks

- ✓ Designed for 60 to 95 tons carriers.
 - ✓ Automatic energy per blow adjustment.
 - ✓ Autonomous working pressure control.
 - ✓ 4.0 breaker.
- **Hydraulic accumulator:** no more regular nitrogen controls and recharges on jobsites.
 - **Made in France:** superior quality steel and manufacturing excellence.
 - **Operator friendly:** blank firing protection, automatic lubrication, energy recovery system, easy maintenance.
 - **Carrier friendly:** anti-vibration dampeners, pressure spikes removal.

Weight and dimensions



Weight kg/lb		
Breaker.	5,208	11,482
+ Mounted tool.	5,771	13,643
+ Mounted adapter plate (max.)	6,803	14,885
Dimensions mm/in		
A.	3,043	119.8
B.	700	27.5
C.	710	28
D.	620	24.5
E.	125	4.9

General specifications

Operating Information

- **Carrier weight range (min-max, mt)** 60 - 95
- **Oil flow (min-max, l/min / gpm)** 400 - 500 / 105.7 - 132
- **Operating pressure (bar/psi)** 180 / 2,611
- **Back pressure (bar/psi)** 15 / 218
- **Input power (kw)** 150
- **Striking frequency (bpm)** 290 - 550
- **Noise level /10m (dba)** 95
- **Automatic lubrication** standard
- **Soundproofing** standard
- **Bucket cylinder valve** standard
- **Pressurization** preinstalled

Options (CPN)


- **Pressurization kit:** 86372505.
- **Adapter plate:** Upon request.
- **Special painting:** Upon request.

Maintenance kits (CPN)

- **Level 0:** 86798311
- **Level 1:** 86798329
- **Level 2:** 101023249

Consumables (CPN)

- **Grease cartridges (x20)** 86784758.
- **Em22 grease bucket (20 kg)** 86383338.
- **Ab1f grease bucket (18 kg)** 101095008.

Tools								
Diameter (mm/in).	214 / 8.43	214 / 8.43	214 / 8.43	214 / 8.43	214 / 8.43	214 / 8.43	214 / 8.43	214 / 8.43
Length (mm/in).	1,845 / 72.63	2,025 / 79.72	1,845 / 72.63	1,845 / 72.63	2,025 / 79.72	2,025 / 79.72	1,845 / 72.63	2,025 / 79.72
Weight (kg/lb).	482 / 1,064	533 / 1,175	463 / 1,022	483 / 1,066	534 / 1,178	535 / 1,180	512 / 1,129	563 / 1,241
CPN.	86792520	86804804	86792553	86759842	86799855	86799863	86792538	86804176

The product designs, specifications and information in this document are provided for informational purposes only and do not constitute warranties of any kind. Product designs and specifications may change at any time without prior notice. The only warranties that apply to the sale of products and services are Komatsu's standard written warranties, which will be provided upon request.

Komatsu and other trademarks used in this document are the property of Komatsu Ltd., Komatsu America Corp., Komatsu Mining Corp. or one of their subsidiaries, or their respective owners or licensees.



komatsulatioamerica.com

