



JTHB290-1


Komatsu Hydraulic Breaker

Sales features

- ✓ Simple design = lower operating costs.
- ✓ Only two moving parts.
- ✓ Accumulator free.
- ✓ Dual retainer pins.
- ✓ Powerful.
- ✓ Auto greasing system (optional).
- ✓ Armor kit (optional).

Specifications

Model	JTHB290-1	
Working weight	2,250	kg
Oil flow	160-200	L/min
Operating pressure	14-18	Mpa
Impact rate	370-490	bpm
Tool diameter	140	mm
Nose size	1	inch
N2 gas pressure	0.8	Mpa
Base machine	20-30	ton



Design concept

Adaptable

- The Komatsu breakers are not sensitive to system back pressure and can be powered by a wide variety of carriers in the field.

User friendly

- Using low pressure nitrogen charge, the Komatsu breaker cushions every blow.
- This reduces wear and tear on the carrier and adds to operator comfort.

Low operating costs

- Featuring only two moving parts and few seals.
- Komatsu breakers offer more "operating-time" along with a simple in the field maintenance.
- When a repair is required the Komatsu breaker will be back on the job quickly and at a reasonable cost.

The product designs, specifications and information in this document are provided for informational purposes only and do not constitute warranties of any kind. Product designs and specifications may change at any time without prior notice. The only warranties that apply to the sale of products and services are Komatsu's standard written warranties, which will be provided upon request.

Komatsu and other trademarks used in this document are the property of Komatsu Ltd., Komatsu America Corp., Komatsu Mining Corp. or one of their subsidiaries, or their respective owners or licensees.

KOMATSU

komatsulatioamerica.com

